



- MMC
- Company Profile
- Products
- SELENIUM Free
- Process
- Sustainability
- Recent developments
- Contact Us
- Search

Go



## Electrolytic Manganese Metal Low Oxygen Flake

Commercial Trade Name: LO

Products

**Size:**  
100% -50mm X down;  
thickness 1.2 mm min, 1.5 mm  
average

Chemical Composition	Guaranteed (%)	
<b>Mn</b> (metallic)*	99.9	min
<b>Mn</b> (total)**	99.6	min
<b>C</b>	0.01	max
<b>S</b>	0.03	max
<b>P</b>	0.002	max
<b>Si</b>	0.01	max
<b>Fe</b>	0.005	max
<b>Cu</b>	0.002	max
<b>Pb</b>	0.001	max
<b>V</b>	0.001	max
<b>Ni</b>	0.001	max
<b>Co</b>	0.001	max
<b>As</b>	0.001	max
<b>N</b>	0.015	max
<b>H</b>	0.025	max
<b>O</b>	0.15	max

\*Total Manganese on a weight basis excluding non metallic elements  
 \*\*Total Manganese on a total weight basis  
 Analytical results are reported as averages and in accordance with ISO 31-0

**NOTE: This product is manufactured using a selenium free process**

Packaging	
500kg	steel drums on pallets
1361kg	in bulk in pallet boxes or 22.68kg paper bags
1000kg	in bulk in pallet boxes or 25kg paper bags
2000kg	in bulk in pallet boxes or 25kg paper bags
1000kg	metal in 25kg paper bags stretch wrapped on pallets
1361kg	metal in 22.68kg paper bags stretch wrapped on pallets

Last updated:31/5/2005

Print this Page Add to Favourites

Developed by Business Connexion